

DINITROL 452

Spray Glue

Characteristics:

DINITROL 452 is a quick-drying glue with a rubber and solvent basis.

Areas of Application:

Particularly suitable for gluing cardboard, felt, paper, expanded rubber, unplasticised synthetic films and vehicle roof lining material onto the same surfaces or other materials, such as wood and metal.

Method of Use:

Spray both parts to be glued, leave to evaporate for approx. 3 minutes and press parts together. Concerning porous or absorbent materials, spray one side and press together immediately, or spray the absorbent part with a fine coat, allow to dry, spray a second coat of glue, leave to dry for 3 – 4 minutes and press parts together.

Technical data:

Colour:	transparent, slightly yellow
Density:	0.705 g/cm ³
Flash point:	< -20°C
Solids content:	approx. 33%
Storage:	cool and dry
Temperature resistant:	80°C short-term 100°C
Storage temperature:	under 25°C
Storage time:	24 months
Delivery form:	400 ml spray can

Note: Opened packages must be used as quickly as possible.

Please refer to the safety data sheet or packaging label for safety instructions.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Telephone:
+49 (0) 52 81 / 9 82 98-0
Fax:
+49 (0) 52 81 / 9 82 98-60
Email:
service@dinol.com