

DINITROL 582

Special Cleaner

DINITROL 582 is a transparent, fast drying cleaner for very dirty surfaces (glass, ceramic-frit, paints, metal, plastics). Clean, non-lipid and by DINITROL 582 pretreated dry surfaces are a precondition for a correct adhesion of the DINITROL bonding system.

- » Excellent cleaner to promote the adhesion of DINITROL bonding system
- » Residuefree cleaning of very dirty surfaces
- » Supports the long term safety of replaced windscreen by DINITROL adhesives



Equipment

INDUSTRIAL NITRILE GLOVES XL 10-P
Art. No. 1734100

DINITROL 582

Art. No.	Size	Package	Color
17357	1 pc.	Towel	White
12044	1 L	Can	Transparent
12145	5 L	Canister	Transparent

a brand of



DINOL GmbH Pyrmonter Straße 76, D-32676 Lügde, Germany
Tel. +49 (0) 5281-98 2 98-0, Fax +49 (0) 5281-98 2 98-60, www.dinol.com

06.2020

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the misuse of our products. Therefore, a contractual legal relationship is not justified, and there are no secondary obligations arising from any purchase contracts.

DINITROL 582

Technical Details

Characteristics

DINITROL 582 is a transparent and fast-drying cleaning agent for heavily soiled surfaces and where conventional cleaning agents are not sufficient to remove tough contaminations and/or residues. DINITROL 582 is an ideal cleaning agent for the removal of dirty surfaces on glasses, ceramic layers, paints, metals but also for plastics. Nevertheless, the compatibility should be tested before use on plastics and other critical surfaces.

Features

- Excellent cleaner to promote the adhesion of the DINITROL bonding system
- Residue-free cleaning of as well heavily soiled surfaces

- Supports the longterm safety of replaced windcreens by adhesives

Application/Method of use

The cleaning process with DINITROL 582 should be done properly with a suitable lint-free cloth or paperliner. If necessary this process must be repeated. Before further processing, for example with DINITROL 538 Plus, the cleaned surfaces must be well vented. This product is suitable for professional experienced users only. To ensure the adhesion and material compatibility outside of the windshield replacements of vehicles, preliminary tests must be done.

Further information:

The following documents are available on request:

- Material safety data sheet

Storage

Storage tightly closed between 0 and 35°C. Use only in well ventilated areas. Storage stability is 12 months.

Technical Data

Base	aliphatic hydrocarbons
Colour	clear/transparent
Density	0,72 g/ml
Flash point	< -4°C
Boiling reange	95 – 100°C
Available in	1 & 5 L, Sachet for one-time-use

For all relevant safety advices please read the material safety data sheet or the packaging label.