

DINITROL VCI UNI 0-40

General Protection

Characteristics:

- Oil base
- Evaporating VCI inhibitors
- For closed systems
- Long term protection

Applications:

DINITROL VCI UNI 40 is suitable for fuel tanks, gear boxes, storage tanks and similar containers. Typical applications are also the protection of outboard-motors during the winter season.

VCI-oil burns without forming ashes and is miscible with gasoline, oil and Diesel. Therefore it is not necessary to take out the DINITROL VCI UNI 0-40 when starting an engine etc. It protects iron, steel, copper, brass, bronze and other metals.

Method of use:

DINITROL VCI UNI 0-40 can be applied by brushing or pouring the product into the parts to be protected. For each m³ of air in the object to be protected about 0,3 – 0,4 l of DINITROL VCI UNI 0-40 oil are needed.

Technical properties:

Colour:	brown transparent
Appearance:	Liquid
Density :	0,90 g/cc
Viscosity, kinematic:	250 cSt
Flash point:	> 130°C
Storage Temperature:	5 – 40°C

For all relevant safety advices please read the material safety data sheet or the packaging label.

Die in diesem Merkblatt gemachten Angaben sind das Ergebnis sorgfältiger Untersuchungen. Soweit sie sich auf die Anwendung beziehen, sind sie als Empfehlung zu betrachten, die dem Erfahrungsstand entsprechen. Wegen der Vielseitigkeit der Anwendungs- und Arbeitsweisen können wir jedoch eine Verbindlichkeit nicht übernehmen. Es wird daher ein vertragliches Rechtsverhältnis nicht begründet, und es entstehen aus eventuellen Kaufverträgen keine Nebenverpflichtungen.

All data and recommendations are the result of careful tests by our laboratories. They only can be considered as recommendation which correspond to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the use of our products.

DINOL GmbH
Pyrmonter Str. 76
D-32676 Lügde
Telefon:
+49 (0) 52 81 / 9 82 98-0
Telefax:
+49 (0) 52 81 / 9 82 98-60
E-Mail:
service@dinol.com